

3M 2214 Masking Tape is a general purpose grade of paper masking tape that offers economical and reliable performance. This grade is manufactured from a crepe paper backing combined with a fast acting rubber based adhesive.

3M 2214 Masking Tape is sliver resistant and can be hand-torn. It is also highly conformable and flexible which allows for accurate application to tight turns and surfaces. It resists paint bleed-through and removes cleanly without leaving unwanted adhesive residue.



Applications

Typical applications for this general purpose grade of masking tape include:

[View This Product](#)

- General purpose masking
- Sealing and bonding
- Bundling and identification of cables

Technical Details

Property	Value
Backing	Crepe Paper
Adhesive Type	Rubber
Colour	Tan / Beige
Total Tape Thickness (ASTM D-3652)	0.14mm
Adhesion to Steel (ASTM D-3330)	24 N/100mm
Tensile Strength (ASTM D-3759)	403 N/100mm
Elongation at Break (ASTM D-3759)	10%
Maximum Temperature (Short-Term, up to 30 Minutes)	93°C

Storage

Store in normal conditions (21°C) and 50% relative humidity.

Shelf Life

For optimum performance, tape should be used within 12 months of supply.

Available Sizes, Forms and Styles

3M 2214 Masking Tape is available in the following standard sizes:

- 18mm Wide x 55 Metres Long
- 24mm Wide x 55 Metres Long
- 36mm Wide x 55 Metres Long
- 48mm Wide x 55 Metres Long

Custom sizes, lengths and request

We're always happy to help with special requirements. If the size you require for your project isn't listed here please do reach out to us. We'll do our very best to help in any way we can.

3M is a registered trademark of 3M.

Important

The values listed here and the information presented should not be treated as a substitute for specific technical advice. We cannot warrant the products performance or suitability for particular applications.

Date Created: 10/10/2016
 Date Modified: 10/10/2016
 Document # SSD-TDS-SWP000014