Important The values listed here and the information presented should not be treated as a substitute for specific technical advice. We cannot warrant the products performance or suitability for particular applications.

swiftsupplies.com.au

Alu Grinding Protection Spray is a specialised technical spray made by Weicon in Germany. This spray is applied directly to grinding and sanding surfaces. There, it acts as a cooling lubricant and separating agent during the grinding process.

Alu Grinding Protection Spray prevents clogging and keeps the pores on the abrasive media open. It forms a anti-adhesive (and silicone-free) layer on the abrasive material that significantly increases the useful life of your abrasive by up to 350%.

Weicon Aluminium Grinding Spray can be used with all kinds of abrasive materials. It works with fibre wheels,

endless grinding belts, sanding sheets, sleeves, orbital sanders and specialised equipment.

Alu Grinding Protection Spray

Technical Data Sheet

This spray is designed to provide greater grinding performance and save you money through extending the life of the abrasive and reducing the frequency with which you need to change it.

Technical Details

Property	Value
Colour	Colourless
Scent	Solvent
Shelf Life (Minimum)	24 Months
Temperature Resistance	-20°C to +130°C

Instructions for Use

Spray a good amount of Alu Grinding Protection directly onto the new abrasion disc ahead of use. Repeat process if grinding performance begins to suffer. Start grinding only after you have allowed time for the propellant to evaporate. Otherwise there is a risk of deflagration.

Storage

Alu Griding Protection Spray is supplied in a pressurised container. It should be stored in a cool, dark place and protected from direct sunlight. Do not expose to temperatures exceeding 50°C.

Available Sizes

Weicon Alu Grinding Protection Spray is available from Swift Supplies Online in 400ml cans.



