

Fibreglass Exhaust Wrap Tape

Technical Data Sheet

Fibreglass Exhaust Wrap Tape is an economical, high temperature insulation material able to withstand ongoing exposure to temperature up to 550°C. This tape has good mechanical strength and is very flexible to allow for tight wrapping around irregularly shaped objects.

Fibreglass Tape has excellent thermal insulation characteristics and effectively dissipates heat. It is resistant to most chemicals and solvents and has high dielectric strength.

This woven Fibreglass Tape does not stretch or shrink and remains inherently stable. At 400°C is retains about 50% of its original tensile strength. Fibreglass Exhaust Wrap Tape will not burn, smoulder or support flame.

Applications

- Wrapping and insulation of exhausts
- Lagging for pipes
- Pipe insulation wrap
- Insulation of cables and hoses
- High temperature gaskets and seals

View This Product

- Oven and boiler door insulation
- Support tape for single sided welding
- General thermal insulation
- Electrical insulation

Property	Value
Basis	Fibreglass Filaments
Adhesive	No
Colour	White
Maximum Operating Temperature	+550°C
Abrasion Resistance	Average
Strength Retention @ 400°C	50%
Strength Retention @ 500°C	25%
Chemical and Solvent Resistance	Good

Technical Details

Important

swiftsupplies.com.au



Technical Data Sheet

swiftsupplies.com.au

Available Sizes

We're pleased to be able to offer our Fibreglass Exhaust Wrap Tape in a selection of sizes.

Standard Sizes

- 1.5mm Thick x 50mm Wide
- 1.5mm Thick x 75mm Wide
- 3mm Thick x 25mm Wide

- 3mm Thick x 40mm Wide
- 3mm Thick x 50mm Wide
- 3mm Thick x 75mm Wide

All of the above sizes are available in either 5 Metre or 30 Metre long rolls.

Custom Sizes

We're always happy to help with special requirements. If the size you require for your project isn't listed here please do reach out to us. We'll do our very best to help in any way we can.