

Fibreglass Exhaust Wrap Insulation Tape

Quick Reference Guide



Overview

Fibreglass Exhaust Wrap Tape is a high temperature insulation cloth cut into convenient and easy to use tape form.

Capable of withstanding ongoing exposure to temperatures of up to 550°C, this woven tape also offers good mechanical strength, thickness consistency and flexibility.

Used for a variety of applications including...

- Wrapping and insulating of exhausts.
- Lagging for pipes.
- Insulation of cables and hoses.
- Support tape for single sided welding.
- Construction of flat high temperature gaskets.
- Oven and Boiler insulation.



Key Specifications

Colour	White
Adhesive	None
Temperature Rating	550°C
Abrasion Resistance	Avg.
Strength Retention @ 400°C	50%

Fibreglass Exhaust Wrap Tape Sizes.

The tables below list all our standard sizes of Fibreglass Insulation Tape in full rolls and 5mtr, pre-cut rolls. To quickly find any on our website, just search for the SWM part number listed.

Alternatively, browse the full range at

swiftsupplies.com.au/fibreglass-exhaust-wrap-insulation-tape-500c-range

Full Rolls, 30 Metres Long

Part Number	Thickness	Width	Roll Length
SWM000037B01V0001	1.5mm	50mm	30 Metres
SWM000037B01V0002	1.5mm	75mm	30 Metres
SWM000037B01V0003	3mm	25mm	30 Metres
SWM000037B01V0004	3mm	40mm	30 Metres
SWM000037B01V0005	3mm	50mm	30 Metres
SWM000037B01V0006	3mm	75mm	30 Metres

Short Rolls, 5 Metres Long

Part Number	Thickness	Width	Roll Length
SWM000037P01V0001	1.5mm	50mm	5 Metres
SWM000037P01V0002	1.5mm	75mm	5 Metres
SWM000037P01V0003	3mm	25mm	5 Metres
SWM000037P01V0004	3mm	40mm	5 Metres
SWM000037P01V0005	3mm	50mm	5 Metres
SWM000037P01V0006	3mm	75mm	5 Metres