

# PTFE Packing Style 3000T

## Quick Reference Guide



### Overview

Our PTFE Packing Style 3000T is a quality, economical grade of gland packing used for sealing in pumps and valves.

This grade of packing is manufactured in the USA with acrylic yarn that are then impregnated with a PTFE lubricant. The result is an interlock braided packing that is extremely tough, dense and long lasting.

Our 3000T is often selected when an economical gland packing is needed for pumps and valves operating at moderate pressure and speeds.

It exhibits reasonable chemical resistance and good compressibility. It is suitable for gland and stuffing box sealing on rotating, centrifugal and reciprocating pumps and all kinds of valves.



### Key Specifications

Base Fibre	Acrylic Impregnated with PTFE
Braid	Interlock
Shaft Speed Rating	11.2 MPS
Pressure Rating	34.5 BAR
Temperature Rating	260°C
pH Range	2-12

### PTFE Packing Style 3000T Sizes.

The table below lists all our standard sizes of Style 3000T PTFE Gland Packing. All are available by the Metre. To quickly find any on our website, just search for the SWM part number listed. Alternatively, browse the full range at [swiftsupplies.com.au/3000T-acrylic-packing-with-ptfe](https://swiftsupplies.com.au/3000T-acrylic-packing-with-ptfe)

Part Number	Size Metric	Size Imperial
<b>SWM000022B01V0001</b>	3.2mm <sup>2</sup>	1/8" Square
<b>SWM000022B01V0002</b>	4.8mm <sup>2</sup>	3/16" Square
<b>SWM000022B01V0003</b>	6.4mm <sup>2</sup>	3/4" Square
<b>SWM000022B01V0004</b>	8mm <sup>2</sup>	1/16" Square
<b>SWM000022B01V0005</b>	9.5mm <sup>2</sup>	3/8" Square
<b>SWM000022B01V0006</b>	12.7mm <sup>2</sup>	1/2" Square
<b>SWM000022B01V0007</b>	16mm <sup>2</sup>	5/8" Square
<b>SWM000022B01V0008</b>	19mm <sup>2</sup>	3/4" Square
<b>SWM000022B01V0009</b>	22mm <sup>2</sup>	7/8" Square
<b>SWM000022B01V0010</b>	25mm <sup>2</sup>	1" Square