

PTFE Packing Style 344

Quick Reference Guide



Overview

Our PTFE Packing Style 344 is a very high-quality grade of pump and valve packing. Style 344 seals with very low friction and is extremely long lasting.

Being made from pure PTFE, 344 Packing also has excellent chemical resistance (0-14 pH) and excellent heat dissipation properties.

This grade is braided using 100% pure PTFE filament that is impregnated with a PTFE suspensoid blocking agent. It has no sacrificial lubricants which wear out over time which enables it to last.

This packing is interlock braided in the USA and is a strong, dense grade which is still flexible enough to offer easy installation.



Key Specifications

Base Fibre	100% PTFE Filament
Braid	Interlock
Shaft Speed Rating	5.1 MPS
Pressure Rating	20.6 BAR
Temperature Rating	260°C
pH Range	0-14 (except strong oxidisers)

PTFE Packing Style 344 Sizes.

The table below lists all our standard sizes of Style 344 PTFE Gland Packing. All are available by the Metre. To quickly find any on our website, just search for the SWM part number listed. Alternatively, browse the full range at [swiftsupplies.com.au/344-100-percent-ptfe-fibre-gland-packing](https://www.swiftsupplies.com.au/344-100-percent-ptfe-fibre-gland-packing)

Part Number	Size Metric	Size Imperial
SWM000252B01V0001	3.2mm ²	1/8" Square
SWM000252B01V0002	4.8mm ²	3/16" Square
SWM000252B01V0003	6.4mm ²	3/4" Square
SWM000252B01V0004	8mm ²	1/16" Square
SWM000252B01V0005	9.5mm ²	3/8" Square
SWM000252B01V0006	12.7mm ²	1/2" Square
SWM000252B01V0007	16mm ²	5/8" Square
SWM000252B01V0008	19mm ²	3/4" Square
SWM000252B01V0009	22mm ²	7/8" Square
SWM000252B01V0010	25mm ²	1" Square