

Chutex Red Lining Rubber

Quick Reference Guide



Overview

Chutex Rubber is a specially developed form of Natural Rubber with excellent wear resistance. This rubber is soft, very flexible, yet also incredibly good at withstanding abrasion or tearing. Chutex is very elastic and is typically used for lining, protection, skirting or sealing.

Chutex has a bright red / pink colouring which makes it very easy to spot. Our Chutex Rubber is a premium, industrial grade rubber that has a smooth surface finish and a shore durometer hardness of 40 Shore A.

Used for a variety of applications including...

- Chute lining, rubber skirts and skirting.
- Wear curtains, dust deflectors.
- As a pipe repair bandage.
- For producing pipe wipers.
- Making drill rod seals.
- Vacuum blankets.
- Pulley lagging.
- Tank linings.
- Conveyor slide guides and curtains.

By the Metre Sizes.

The table below lists all our standard sizes of Chutex Rubber that are available by the metre. To quickly find any on our website, just search for the SWM part number listed. Alternatively, browse the full range at swiftsupplies.com.au/chutex-rubber/

Thickness	Part Number	Width
1.5mm	SWM000227B01V0001	1200mm
3mm	SWM000227B01V0002	1200mm
4.5mm	SWM000227B01V0003	1200mm
6mm	SWM000227B01V0004	1200mm
9mm	SWM000227B01V0005	1500mm
12mm	SWM000227B01V0006	1500mm
19mm	SWM000227B01V0007	1500mm

Custom Chutex Rubber Gaskets, Strips, Seals and Parts.

We are pleased to offer custom-cut Chutex components to suit various applications. These include custom sized gaskets, strips, washers, and more cut from this material. For more information on custom Chutex components, please do contact us.



Key Specifications

Temperature Rating	-20°C to 70°C
Colour	Reddish Pink
Insertion	None
Polymer	Natural Rubber
Hardness	40 (±5) Shore A
Elongation at Break	550%
Specific Gravity	1.05
Tear Strength	60 N / mm
Abrasion	95mm ³ (max.) @ 5N

