

Overview

Concrete Repair Stick is the fast, simple and easy way to make repairs to concrete, bricks, sandstone, stone and all kinds of masonry.

Manufactured from epoxy resin filled with ceramic fibres, Concrete Repair Sticks are soft and pliable when you take them out of the tube but, once applied, sets hard like concrete.

They are grey in colour so that they match their surrounds and can be used indoors and outdoors.

Typical applications include:

- Repairs to chipped or broken brickworks, concrete slabs, stone and tiles.
- Crack filling and repair.
- Secure chipped or broken off parts.
- Repairs to statues, curbstones, borders and ornaments.
- Smooth out unwanted steps or irregular surfaces.
- Repair and fixing of marble, granite, sandstone and more.
- Also used for repairs to ceramic surfaces, glass, metal, wood and many plastics.
- Bonding and fixing broken pavers back into place.



Concrete Repair Stick Sizes.

To quickly find any on our website, just search for the SWM part number listed. Alternatively, browse the full range at [swiftsupplies.com.au/concrete-repair-sticks-range](https://www.swiftsupplies.com.au/concrete-repair-sticks-range)



Key Specifications

Colour	Grey
Continuous Temperature Rating	-50°C to +120°C
Basis	Epoxy w/ Ceramic
Pot Life	6 Minutes
35% Cure / Handling	15 Minutes
100% Cure / Full	24 Hours
Shore Hardness	80 Shore D

Material Compatibility

Metal (e.g. stainless steel, brass, cast iron, aluminium)	Compatible
Hard Plastics* (e.g. epoxy laminates, rigid PVC)	Compatible
Wood (e.g. oak, beech, spruce, balsa)	Compatible
Derived Timber Products (e.g. plywood, MDF)	Compatible
Fibre Reinforced Materials (e.g. GFRP, CFRP, Fibreglass)	Compatible
Glass, Ceramic	Compatible
Stone (e.g. granite, brick, concrete, marble)	Highly Compatible
Rubbers	Not Compatible

*Bonding to plastics will depend on the type. Low surface energy plastics may not be suitable (e.g. PE, PP, PTFE).

Part Number	Size
SWM000020B01V0001	57gm
SWM000020B01V0002	115gm