

Overview

Contractors Silicone is a one part, acetoxy cure silicone adhesive and sealant with excellent adhesion to a wide range of materials.

This economical grade offers good all-round performance and is easy to use.

It offers good long term reliability for glazing and sealing applications and has excellent resistance to degradation from UV and weathering.

Contractors Silicone sealant is fast curing (around 5-10 minutes for skin-over) and is used in temperatures between -60°C and 180°C.

It is non-slumping and allows for dynamic joint movement of up to 25% while maintaining sealing integrity. Contractors Silicone is 5 star VOC compliant.

Typical applications include...

- Sealing refrigerated rooms
- Sealing ventilation and air conditioning ducting and equipment
- Construction and sealing of metal and plastic signs
- Sealing around skylights and windows
- Glazing of panels and frames
- General bonding and sealing of metals, aluminium, glass, wood, ceramics and many plastics



Key Specifications

Basis	Acetate Silicone
Viscosity	Pasty
Specific Gravity	1.04
Sag / Slump	Non-Slump
Skin-Over	5-10 Minutes
Hardness	28 Shore A
Dynamic Joint Movement	25%
Temperature Rating	-62°C to +180°C

Contractors Silicone Standard Sizes.

The table below lists all our standard sizes of our Contractors Silicone. To quickly find any on our website, just search for the SWM part number listed. Alternatively, browse the full range at swiftsupplies.com.au/contractors-general-purpose-silicones-range

Part Number	Colour	Size
SWM000090B01V0001	Black	300gm
SWM000090B01V0002	Transparent	300gm
SWM000090B01V0003	White	300gm