

GMK 2410 Contact Adhesive

Quick Reference Guide



Overview

GMK 2410 Rubber Metal Contact Adhesive is an industrial-grade adhesive designed specifically for bonding rubber to metal and rubber to rubber. This high strength adhesive is used to create permanent, strong bonds.

In addition to its excellent compatibility with rubber and metal, GMK 2410 also works very well with cellular rubber (like our Neoprene Sponge Sheet), felt, insulation material, textiles, wood and many different types of plastic.

Typical applications include:

- Bonding rubber pads and sheet to metal wall structures, posts and piping.
- Sticking rubberised sponge and foam to metal supports
- Laminating different thicknesses of rubber sheet and sponge
- Gluing down rubber sheet to metal trays and plates
- Laminating felt to form new thicknesses or bonding felt to metal
- Gluing rubber to wood



Key Specifications

Colour	Yellowish – Brown
Viscosity	2,400 MPa·s
Contact Adhesion	10 Minutes
Temperature Rating	-40°C to +80°C
Consumption	250 – 350g / m ² (approx.)
Gal. Steel to EPDM	0.16 N/mm ²
Gal. Steel to Gal. Steel	1.6 N/mm ²
Gal. Steel to Nitrile	0.54 N/mm ²

GMK 2410 Contact Adhesive Standard Sizes.

The table below lists all our standard sizes of GMK 2410 Rubber Metal Contact Glue. To quickly find any on our website, just search for the SWM part number listed. Alternatively, browse the full range at [swiftsupplies.com.au/gmk-2410-contact-adhesives-range](https://www.swiftsupplies.com.au/gmk-2410-contact-adhesives-range)

Part Number	Container Size	Pack Type
SWM000125B01V0001	185gm	Squeeze Tube
SWM000125B01V0003	350gm	Brush Top Can
SWM000125B01V0004	700gm	Can
SWM000125B01V0005	5kg	Bucket
SWM000125B01V0006	25kg	Bucket