Graphite Packing Style 5000 (100% Graphite) Quick Reference Guide



Overview

Our Graphite Packing Style 5000 is a versatile style of graphite pump and valve packing. This style is made using high purity graphite yarns that are plait braided to form a tough, durable gland packing material.

Since it is made with pure graphite, Style 5000 is self-lubricating and generates very low rates of friction even at high speeds. It is able to handle shaft speeds up to 20 MPS (4,000 FPM). It's pressure rating varies depending on whether it is installed in a pump of valve. In pumps, it is rated to 207 BAR while in pumps this number is 34 BAR.

One of the main benefits associated with this high-quality graphite packing is its' virtually leak free sealing performance. It achieves this by forming a homogenous mass under gland pressure. This results in maximum sealability and a reduction in flush water usage.

Being made from pure graphite, Style 5000 has excellent heat dissipation properties.



Key Specifications

Base Fibre	100% Expanded Graphite	
Braid	Plait	
Shaft Speed Rating	20 MPS	
Pressure Rating	34 BAR in Pumps 207 BAR in Valves	
Temperature Ratings	455°C in Air (850°F) 649°C in Steam (1200°F) 3315°C in Non-Oxidising Atmospheres	
pH Range	0-14	

Graphite Packing Style 5000 Sizes.

The table below lists all our standard sizes of Style 5000 Graphite Gland Packing. All are available by the Metre. To quickly find any on our website, just search for the SWM part number listed. Alternatively, browse the full range at swiftsupplies.com.au/5000-100-percent-graphite-packing

Part Number	Size Metric	Size Imperial
SWM000220B01V0001	3.2mm ²	1/8" Square
SWM000220B01V0002	4.8mm²	3/16" Square
SWM000220B01V0003	6.4mm ²	3/4" Square
SWM000220B01V0004	8mm²	/16" Square
SWM000220B01V0005	9.5mm²	3/8" Square
SWM000220B01V0006	12.7mm²	1/2" Square
SWM000220B01V0007	16mm²	5/8" Square
SWM000220B01V0008	19mm²	3/4" Square
SWM000220B01V0009	22mm²	7/8" Square
SWM000220B01V0010	25mm²	1" Square