

### Overview

Aramid Fibre Tape is a tough, strong and flexible tape that is able to withstand extremely demanding physical stress and high temperatures. It is manufactured from fibreglass core yarn coated with aramid fibres.

Identifiable by its distinctive yellow colour, this tape can withstand temperatures up to 340°C.

Used for a variety of applications including...

- Pipe and hose insulation and lagging where high abrasion resistance is required
- Making wicks for fire twirling equipment
- Oven door sealing
- Strapping and wrapping in elevated temperatures
- High temperature gaskets and seals
- Making expansion joints and bellows
- General thermal insulation
- Electrical insulation



### Key Specifications

Colour	Yellow
Adhesive	None
Temperature Rating	340°C
Abrasion Resistance	Excellent
Strength Retention @ 260°C	54%

### Aramid Tape Sizes.

The tables below list all our standard sizes of Aramid Insulation Tape in full rolls and by the metre. To quickly find any on our website, just search for the SWM part number listed. Alternatively, browse the full range at [swiftsupplies.com.au/aramid-kevlar-insulation-tape-340c](https://www.swiftsupplies.com.au/aramid-kevlar-insulation-tape-340c)

Thickness	Width	Full Roll (30 Metres)	By the Metre
0.8mm	25mm	SWM000017B01V0001	SWM000017P01V0001
0.8mm	50mm	SWM000017B01V0005	SWM000017P01V0005
1.5mm	25mm	SWM000017B01V0002	SWM000017P01V0002
1.5mm	50mm	SWM000017B01V0006	SWM000017P01V0006
3mm	25mm	SWM000017B01V0003	SWM000017P01V0003
3mm	40mm	SWM000017B01V0004	SWM000017P01V0004
3mm	50mm	SWM000017B01V0007	SWM000017P01V0007
3mm	75mm	SWM000017B01V0008	SWM000017P01V0008