

### Overview

PetroGard Tape ST is a high-quality corrosion protection tape.

Used either independently, or as part of the wider PetroGard corrosion protection system, this tape is easy to work with and very effective.

PetroGard ST is manufactured using a non-woven polyester fabric carrier which is fully saturated and impregnated with a petrolatum compound, blended with inert fillers, corrosion inhibitors and spectrum biocide. It is made in accordance with AWWA (American Water Works Association) standard C217-04.

This quality corrosion protection tape offers excellent resistance to acids, alkalis and bacteria. It will not polymerise or oxidise. It is also non-hardening which allows it to accommodate substrate vibration and movement whilst still maintaining protection.

Used for a variety of applications including...

- Corrosion protection for piping located above or below ground.
- Protecting submerged pipes and fittings.
- Corrosion protection for tie rods and starter bars.
- As an isolation tape for roof sheeting.



### Key Specifications

Thickness	1.4mm (Average)
Tear Strength	35.8 N (Lengthwise) 32.9 N (Across Roll)
Break Strength	186 N (Lengthwise) 58.2 N (Across Roll)
Temperature Rating	-10°C to +50°C
Service Life	30 Years +
Roll Length	10 Metres

### Petro Tape ST Standard Sizes and Info.

The tables below list all our standard sizes of our PetroGard ST Corrosion Protection Tape. To quickly find any on our website, just search for the SWM part number listed. Alternatively, browse the full range at [swiftsupplies.com.au/corrosion-protection-tapes](https://swiftsupplies.com.au/corrosion-protection-tapes)

Part Number	Roll Width
<b>SWM000209B01V0001</b>	50mm
<b>SWM000209B01V0002</b>	75mm
<b>SWM000209B01V0003</b>	100mm
<b>SWM000209B01V0004</b>	150mm