

# Super-Tack Adhesive Sealant Quick Reference Guide



## Overview

Super-Tack is a professional grade adhesive sealant with a very high initial bond strength. Based on MS Polymers, it is completely free of silicones, isocyanate, halogens and solvents.

It is compatible with most types of materials and surfaces. These include metal, wood, glass, stone, ceramic and the vast majority of plastics.

Super-Tack is typically used for jobs that require a high strength adhesive sealant that will bond fast.

It is used to bond vertically aligned surfaces and parts and will tolerate larger bonding gaps (up to 10mm deep by 30mm wide) without sacrificing bond strength.

This premium grade adhesive sealant has been engineered by Weicon in Germany and is very long lasting. Once fully cured, it will be highly resistant to UV and weathering which makes it ideal for bonding and sealing outdoors.

Typical applications include...

- Drywall and interior construction, renovation, and DIY work.
- Boat and yacht construction and repairs.
- Bonding and sealing ventilation and air conditioning ducting and parts.
- General engineering and facilities maintenance.
- Metal construction and fabrication.
- Anywhere adhesive sealants containing silicone are not allowed.

## Super-Tack Information.

The table below lists all our standard sizes of Weicon Super Tack. To quickly find any on our website, just search for the SWM part number listed. Alternatively, browse the full range at [swiftsupplies.com.au/super-tack-adhesive-sealants-range](https://swiftsupplies.com.au/super-tack-adhesive-sealants-range)



## Key Specifications

Basis	1 Part MS Polymer
Viscosity	Pasty
Density	1.62 g/cm <sup>3</sup>
Skin-Over	10 Minutes
Hardness	50 Shore A
Elongation	600%
Max. Movement	20%
Continuous Temp.	-40°C to +90°C



Part Number	Colour	Cartridge Size
<b>SWM000170B01V0001</b>	Grey	290ml
<b>SWM000170B01V0002</b>	White	290ml