

Overview

Our Viton O Ring Cord is a high quality, industrial-grade product designed for the most demanding of applications. This extruded rubber cord is used for sealing in the most extreme environments that any rubber can handle and exhibits excellent chemical resistance, heat resistance and mechanical properties.

We are pleased to offer this premium O Ring cord in a variety of sizes; all available by the metre. All of our Black Viton O Ring Cord is manufactured in the USA from high quality compounds and produced to tight dimensions tolerances.

Viton is typically specified for applications that require the sealing performance and compressibility of a rubber but the capacity to withstand attack from corrosive media. In these applications, Viton has no peers amongst rubber compounds and exhibits the most wide-ranging, reliable chemical resistance of any known type of elastomer.

Viton Rubber O Ring Cord Sizes.

The table below lists all our standard sizes of Black Viton O Ring Cord. All are available by the metre. To quickly find any on our website, just search for the SWM part number listed. Alternatively, browse the full range at swiftsupplies.com.au/Viton-O-Ring-Cord-Range



Key Specifications

Colour	Black
Polymer	Viton Rubber (FKM)
Hardness	70 Shore A
Temperature Rating	-15°C to +260°C

Part Number	Cord Diameter
SWM000330B01V0001	3.2mm
SWM000330B01V0002	3.5mm
SWM000330B01V0003	4.8mm
SWM000330B01V0004	5mm
SWM000330B01V0005	6.4mm
SWM000330B01V0006	7mm

Part Number	Cord Diameter
SWM000330B01V0007	8mm
SWM000330B01V0008	9.5mm
SWM000330B01V0009	12.7mm
SWM000330B01V0010	14.2mm
SWM000330B01V0011	15mm
SWM000330B01V0012	19mm