

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Name of product Easy-Mix S 50 Resin
Code-Nr. 106501

1.2. Relevant identified uses of the substance or mixture and uses advised against**Recommended intended purpose(s)**

2-Component Epoxy Resin - Resin Component

1.3. Details of the supplier of the safety data sheet**Distributor**

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone +49(0)251 / 9322 - 0, Fax +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone +49(0)251 / 9322 - 0
Fax +49(0)251 / 9322 - 244
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

| Hazard classes and Hazard categories | Hazard Statements | Classification procedure |
|--------------------------------------|-------------------|--------------------------|
|--------------------------------------|-------------------|--------------------------|

| | | |
|-------------------|------|--|
| Skin Irrit. 2 | H315 | |
| Eye Irrit. 2 | H319 | |
| Skin Sens. 1 | H317 | |
| Aquatic Chronic 2 | H411 | |

Hazard Statements

| | |
|------|--|
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H411 | Toxic to aquatic life with long lasting effects. |

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS07



GHS09

Signal word

Warning

Hazard Statements

| | |
|------|--|
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H411 | Toxic to aquatic life with long lasting effects. |

Precautionary Statements

| | |
|--------------------|--|
| P102 | Keep out of reach of children. |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
| P264 | Wash hands thoroughly after handling. |
| P272 | Contaminated work clothing should not be allowed out of the workplace. |
| P273 | Avoid release to the environment. |
| P302 + P352 | IF ON SKIN: Wash with plenty of soap and water. |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P332 + P313 | If skin irritation occurs: Get medical advice/attention. |
| P337 + P313 | If eye irritation persists: Get medical advice/attention. |
| P362 | Take off contaminated clothing. |
| P363 | Wash contaminated clothing before reuse. |
| P391 | Collect spillage. |
| P501 | Dispose of contents/container to hazardous or special waste collection point. |

Hazardous ingredients for labeling

Bisphenol F - epichlorhydrin resin with Number average Molecular Weight < 700, reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

Special rules for supplemental label elements for certain mixtures

Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards**Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/ information on ingredients**3.1. Substances**

not applicable

3.2. Mixtures**Description**

Resin for a two-component epoxy adhesive



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 21.12.2017

revision 28.07.2017 (GB) Version 8.7

Easy-Mix S 50 Resin

Hazardous ingredients

| CAS No | EC No | Name | [% weight] | Classification according to Regulation (EC) No 1272/2008 [CLP/GHS] |
|------------|-----------|---|------------|---|
| 25068-38-6 | 500-033-5 | reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700) | 70 - 90 | Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411 |
| 28064-14-4 | 608-164-0 | Bisphenol F - epichlorhydrin resin with Number average Molecular Weight < 700 | 1 - 10 | Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411 |

REACH

| CAS No | Name | REACH registration number |
|------------|---|---------------------------|
| 25068-38-6 | reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700) | 01-2119456619-26-xxxx |

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately and dispose it safely.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

After eye contact, rinse opened eye for 15 minutes under running water. Transfer to hospital for specialist examination.

In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

Rinse out mouth and give plenty of water to drink.

4.2. Most important symptoms and effects, both acute and delayed

Physician's information / possible symptoms

vomiting

Respiratory complaints

Nausea

Confusion

skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treatment (Advice to doctor)

Keep under medical supervision for at least 48 hours.

Symptoms may not occur until several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam

Dry fire-extinguishing substance

Carbon dioxide

Water spray jet



Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

Carbon dioxide (CO₂)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, sawdust).

After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

**Easy-Mix S 50 Resin****7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep in closed original container.

Advice on storage compatibility

Do not store with acids or alkalis.

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with oxidizing agents.

Further information on storage conditions

Protect from direct solar radiation.

Store container at cool and aired place.

Store in a dry place.

Protect from heat/overheating.

7.3. Specific end use(s)**Recommendation(s) for intended use**

See section 1.2

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****DNEL-/PNEC-values****DNEL worker**

| CAS No | Substance name | Value | Code | Remark |
|------------|---|-------------------------|--------------------------------------|--------|
| 25068-38-6 | reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700) | 12,25 mg/m ³ | DNEL long-term inhalative (systemic) | |
| | | 8,33 mg/kg bw/day | DNEL long-term dermal (systemic) | |
| | | 8,33 mg/kg bw/day | DNEL long-term dermal (local) | |

PNEC

| CAS No | Substance name | Value | Code | Remark |
|------------|---|--------------|-----------------------------------|--------|
| 25068-38-6 | reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700) | 0,006 mg/l | PNEC aquatic, freshwater | |
| | | 0,0006 mg/l | PNEC aquatic, marine water | |
| | | 0,0996 mg/kg | PNEC sediment, marine water | |
| | | 10 mg/l | PNEC sewage treatment plant (STP) | |
| | | 0,996 mg/kg | PNEC sediment, freshwater | |

8.2. Exposure controls**Respiratory protection**

If ventilation insufficient, wear respiratory protection.

Breathing apparatus in the event of aerosol or mist formation.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: natural rubber, 0,6mm; 480min; 60min;

**Easy-Mix S 50 Resin**

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

! SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

liquid

Colour

yellow, clear

Odour

hardly noticeable

Odour threshold

not determined

Important health, safety and environmental information

| | Value | Temperature | at | Method | Remark |
|---------------------------------------|------------------------|-------------|----|--------|-----------------------------------|
| pH value | not determined | | | | |
| boiling point | > 200 °C | | | | |
| Melting point / Freezing point | not determined | | | | |
| Flash point | > 150 °C | | | | |
| Vapourisation rate | not determined | | | | |
| Flammable (solid) | not determined | | | | |
| Flammability (gas) | not determined | | | | |
| Ignition temperature | not determined | | | | |
| Self ignition temperature | | | | | The product is not self-igniting. |
| Lower explosion limit | not determined | | | | |
| Upper explosion limit | not determined | | | | |
| Vapour pressure | not determined | | | | |
| Relative density | 1,17 g/cm ³ | 20 °C | | | |
| Vapour density | not determined | | | | |
| Solubility in water | | | | | insoluble |
| Solubility/other | not determined | | | | |

**Easy-Mix S 50 Resin**

| | Value | Temperature | at | Method | Remark |
|--|---------------------------|-------------|----|--------|--------|
| Partition coefficient n-octanol/water (log P O/W) | not determined | | | | |
| Decomposition temperature | not determined | | | | |
| Viscosity kinematic | 8000 - 15000 mPa*s | 25 °C | | | |
| Viscosity dynamic | not determined | | | | |
| Oxidising properties | No information available. | | | | |
| Explosive properties | No information available. | | | | |
| 9.2. Other information | No information available. | | | | |

! SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Reactions with strong acids.

Reactions with strong alkalies and oxidising agents.

10.4. Conditions to avoid

Thermal decomposition can lead to the escape of irritating gases and vapours.

Keep away from heat.

10.5. Incompatible materials**Substances to avoid**

Alkali (lye), concentrated

Acid, concentrated

Oxidising agent, strong

10.6. Hazardous decomposition products

Nitrogen oxides (NOx)

Carbon monoxide and carbon dioxide.

Thermal decomposition

Remark No decomposition if used as directed.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

| | Value/Validation | Species | Method | Remark |
|---------------------------|------------------|---------|--------|-----------------|
| LD50 acute oral | 11400 mg/kg | rat | | CAS: 25068-38-6 |
| LD50 acute dermal | > 20 ml/kg | rabbit | | CAS: 25068-38-6 |
| Skin irritation | irritant | | | |
| Eye irritation | irritant | | | |
| Skin sensitization | sensitizing | | | |

Experiences made from practice

Sensitization through skin contact possible.
Irritates eyes and skin.

Additional information

The product is to be handled with the caution usual with chemicals.
Other hazardous properties may not be excluded.

SECTION 12: Ecological information**12.1. Toxicity**

No information available.

12.2. Persistence and degradability

| Elimination rate | Method of analysis | Method | Validation |
|---------------------------------|--------------------|--------|----------------|
| Biological degradability | | | not degradable |

12.3. Bioaccumulative potential

Insoluble in water

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects**General regulation**

Toxic to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

The ecotoxic effect of the product has not been tested. The information on this was derived from products of similar structure or composition.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Recommendations for the product**

Cured material may be considered inert and disposed of as builders waste.

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

Untamminated packaging may be treated as household waste.

SECTION 14: Transport information

| | ADR/RID | IMDG | IATA-DGR |
|---|---|---|---|
| 14.1. UN number | 3082 | 3082 | 3082 |
| 14.2. UN proper shipping name | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N. O.S. (BISPHENOL A EPOXY HARZ) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN) | Environmentally hazardous substance, liquid, n.o.s. (BISPHENOL A EPOXY RESIN) |
| 14.3. Transport hazard class(es) | 9 | 9 | 9 |
| 14.4. Packing group | III | III | III |
| 14.5. Environmental hazards | Yes | Yes | Yes |

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 9

tunnel restriction code E

Classification code M6

Marine transport IMDG

MARINE POLLUTANT

Transport/further information

Marine pollutant: NO

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard**

VOC content 0 %

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.6

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.