

Our Top-Lube Fluid Spray is an industrial grade spray-on lubricant developed especially for food grade applications. This lubricating spray is made from synthetic oils and is engineered to be safe, reliable and very effective.

Manufactured by Weicon in Germany, Top-Lube Fluid Spray has several features that have led to its use in sensitive applications and industries around the world. These are expanded on in the following sections:

### **NSF Approved for Use in the Food and Beverage Sectors.**

Weicon Top-Lube Fluid Spray is classified as an NSF H2 product (registration 152617). This allows it to be used in a variety of applications in food and beverage processing for reducing wear, friction and noise.

[View This Product](#)



### **Excellent Adhesion and Pressure Resistance.**

Our Top-Lube Fluid Spray sticks where its sprayed so it can continue to lubricate treated parts and surfaces. It resists displacement due to pressure and friction and bonds well to all kinds of materials including plastics, metals and more.

This spray-on lubricant also features excellent penetration (creep) to effectively flow into small or hard to reach areas.

### **Noise Dampening.**

Top-Lube Fluid has good noise dampening characteristics. Part of this is due to the lubrication effect, part due to its formulation. This spray helps reduce noise from moving parts on all kinds of machines and equipment.

### **Water Repellent.**

Another feature of Top-Lube Fluid is its water repellence. The lubricating residue left by this spray prevents water ingress.

### **High Temperature Resistance.**

Top-Lube Fluid Spray is used in a wide range of applications partly thanks to its excellent temperature resistance. Once applied, this lubricating spray can withstand conditions between -20°C and +250°C.

### **Prevents Elongation, Friction and Wear.**

Used on all kinds of moving parts, the high lubrication effect of Top-Lube Fluid helps keep parts functioning long. It reduces friction and elongation which, in turn, helps to reduce wear and increase service life.

---

**Important**

The values listed here and the information presented should not be treated as a substitute for specific technical advice. We cannot warrant the products performance or suitability for particular applications.

Date Created: 29/2/2020

Date Modified: 29/2/2020

Document # SSD-TDS-SWM000190

**Common Applications for Top-Lube Fluid Spray.**

Due to its NSF registration, Top-Lube Fluid is a popular choice for all kinds of spray on lubrication jobs in the food, beverage and pharmaceutical industries around the world. Some of the parts often lubricated with this spray include:

- Toothed Wheels.
- Worm Gears.
- Joints and Couplings.
- Rollers.
- Bearings.
- Chains and Wire Cables.
- Spring Assemblies.

**Technical Details**

<b>Property</b>	<b>Value</b>
Colour	Slightly Yellowish, Transparent
Scent	Neutral
Shelf Life (Minimum)	12 Months
Temperature Resistance	-20°C to +250°C

**Storage**

Top-Lube Fluid Spray is supplied in a pressurised container. It should be stored in a cool, dark place and protected from direct sunlight. Do not expose to temperatures exceeding 50°C.

**Available Sizes**

Weicon Top-Lube Fluid Spray is available from Swift Supplies Online in 400ml cans.

**Important**

The values listed here and the information presented should not be treated as a substitute for specific technical advice. We cannot warrant the products performance or suitability for particular applications.

Date Created: 29/2/2020  
Date Modified: 29/2/2020  
Document # SSD-TDS-SWM000190