

Our Universal Spray-On Grease with MoS2 is a professional-quality grease spray. Manufactured by Weicon in Germany, this lubricant is resistant to high pressures and offers good, long term performance.

Universal Spray-On Grease with MoS2 is black in colour and able to withstand temperatures between -20°C and +120°C. It adheres to most materials and surfaces to form a low friction, robust layer that helps to prevent seizing, reduce wear and increase efficiency.

Made with a high-quality grade of Molybdenum Disulfide (sometimes known as a Moly), this lubricating grease spray is used in all kinds of industrial applications around the world.



[View The Product Page](#)

This moly coating spray can be used with a large range of different components and parts. These include:

- Rolling and Slide Bearings.
- Joints.
- Levers.
- Sliding Guides.
- Spindles.
- Camshafts.
- Spline Shafts.
- Springs.
- Exposed Gears.
- Worm Gears

Technical Details

Property	Value
Colour	Black
Smell	Almost Odourless
Temperature Resistance	-20°C to +120°C
Minimum Shelf Life	24 Months
ISSA Reference	53.402.51
IMPA Reference	45 08 34

Instructions for Use

Clean and dry the surfaces before application. Shake can until mixing ball can be heard. Spray on from about 15cm.

Storage

Universal Spray-On Grease with MoS2 is supplied in a pressurised container. It should be stored in a cool, dark place and protected from direct sunlight. Do not expose to temperatures exceeding 50°C.

Available Sizes

Weicon Universal Spray-On Grease with MoS2 is available from Swift Supplies Australia in 400ml cans.

Important

The values listed here and the information presented should not be treated as a substitute for specific technical advice. We cannot warrant the products performance or suitability for particular applications.

Date Created: 1/7/18

Date Modified: 1/7/18

Document # SSD-TDS-SWP000136