Technical Data Sheet

Our W44T Multi-Spray Fluid NSF is a specialised variant of our popular W44T Multi-Spray that has been reengineered to meet the needs of the food, beverage and pharmaceutical industries.

This spray combines several distinct features into one. It dissolves rust, prevents corrosion and is a powerful penetrating oil with excellent lubricating properties. It is also an excellent cleaner, preservation agent and water displacement spray.

NSF H1 Food Grade Penetrating Lubricant.

W44T Multi-Spray Fluid is certified as an NSF H1 approved lubricating spray. This allows it to be used in all sorts of

applications in the food processing, beverage manufacturing, pharmaceutical and cosmetic industries.

NSF H1 approval allows W44T Multi-Spray Fluid to be used on machines and surfaces where incidental contact with foodstuffs is possible.

Common Applications for W44T Multi-Spray Fluid NSF.

This food grade penetrating oil, lubricant, cleaner, preservation agent & rust removal spray is widely used in all kinds of industries around the world. Some of the more common ones we've seen in Australia (or heard about elsewhere) include:

- Lubricating moving parts on machines used in meat processing.
- Protecting tools and spare parts from corrosion while being stored.
- Removing moisture from electrical fittings and connections.
- Stopping hinges from squeaking.
- Lubricating the movement of rollers on beverage processing lines.
- Lubricating bearings on food processing machines.
- Cleaning and protecting surfaces used in pharmaceutical labs.
- Preventing leakage current and easing the start-up of electric motors kept in wet or humid conditions.
- Removing rust from corroded parts.
- Loosening seized screws, bolts, fittings, locks and valves.
- Cleaning and protecting metal in commercial kitchens and bars.



swiftsupplies.com.au







Technical Data Sheet

Technical Details

Property	Value
Colour	Beige
Scent	Almost Odourless
Shelf Life (Minimum)	24 Months
Temperature Resistance	-20°C to +150°C

Processing

Spray onto the part being treated and allow time to react. If necessary, wipe off with a clean cloth. Repeat process as required. Avoid contact with plastic or varnished surfaces.

Storage

W44T Fluid Spray is supplied in a pressurised container. It should be stored in a cool, dark place and protected from direct sunlight. Do not expose to temperatures exceeding 50°C.

Available Sizes

W44T Fluid Spray is available from Swift Supplies Online in 400ml cans.

Important