

Workshop Cleaner



free of solvents and phosphate bio-degradable

Workshop Cleaner cleans and degreases all metals, plastics, types of rubber, glass, ceramics and wood. It removes grease, oil, resin, rust, wax, nicotine, insect dirt, bitumen and tar specks.

Workshop Cleaner is free of solvent, emulsifier and phosphate compatible with oil separators (ÖNORM B 5105) and, in accordance with EC-guidelines, bio-degradable. It is highly concentrated and can be diluted to the proportion 1:40 (max.).

Workshop Cleaner contains selected foamless tensides and, in addition to manual cleaning, can be used in highpressure cleaners, part washing machines and spray apparatuses (e.g. Pump Dispenser WPS 1500).

Storage

Keep in closed original container. Protect from direct sun light. Storage temperature may not exceed +50°C. Store container in a cool, dry and ventilated place.

Safety and health

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes:

15205001	۱
15205500	۱
15205005	۱
15205010	۱
15205028	١

Workshop Cleaner 1 L Workshop Cleaner 500 ml Workshop Cleaner 5 L Workshop Cleaner 10 L Workshop Cleaner 28 L

Accessories:

Addeddonied.	
15830001	Adjusting Valve for cans, 5 L & 10 L
15831001	Adjusting Valve for cans, 28 L
15841500	Pump-Dispenser WPS 1500, 1,5 L
15841501	Extension for WPS 1500,
15842001	Pump Dispenser,

Technical Data

Odour	almost odourless
Storage stability	24 months
Features	solvent-free, biodegradable
Colour	blue
AOX-free*	Yes
Temperature resistance	+5 to +90 °C
Suitable for application with	WPS 1500
ISSA-Code	53.402.36/37/38
IMPA-Code	551577/78/79

* AOX = Adsorbable Organic Halides (chlorine, bromine and iodine compounds)

Processing

Apply Workshop Cleaner generously to the parts that need to be cleaned, allow it to soak in and wipe it off with a clean cloth. Repeat this action in the event of stubborn stains. The cleaning process can be shortened by warming up the product (max. +90°C). Particularly coarse dirt can be removed more simply in this way. Do not apply it undiluted to aluminium or zinc coatings (alkaline, concentrated pH value approx. 12). Protect against frost.

Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON GmbH & Co. KG (Headquarters) Germany phone +49 (0) 251 9322 0 info@weicon.de www.weicon.de

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za www.weicon.co.za

WEICON Middle East L.L.C. United Arab Emirates phone +971 4 880 25 05 info@weicon.ae www.weicon.ae

WEICON South East Asia Pte Ltd Singapore phone (+65) 6710 7671 info@weicon.com.sg www.weicon.com.sg

WEICON Inc. Canada phone +1 877 620 8889 nfo@weid www.weicon.ca

WEICON Czech Republic s.r.o. Czech Republic phone +42 (0) 417 533 013 info@weicon.cz www.weicon.cz

WEICON Kimya Sanayi Tic. Ltd. Şti. Turkey phone +90 (0) 212 465 33 65 info@weir www.weicon.com.tr

WEICON Ibérica S.L. Spain phone +34 (0) 914 7997 34 info@weicon.es www.weicon.es

WEICON Romania SRL Romania phone +40 (0) 3 65 730 763 office@wei www.weicon.com.ro

WEICON Italia S.r.I. Italy phone (+39) 0102924871 info@weicon www.weicon.it